

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-306853

(43)Date of publication of application : 22.11.1996

(51)Int.Cl.

H01L 23/50

H01L 21/60

H01L 23/12

H01L 23/28

(21)Application number : 07-110380

(71)Applicant : FUJITSU LTD

(22)Date of filing : 09.05.1995


(72)Inventor : HAYASHIDA KATSUHIRO
SATO MITSUTAKA
UNO TADASHI
FUJISAWA TETSUYA
WAKI MASAKI

(54) SEMICONDUCTOR DEVICE, MANUFACTURE THEREOF AND MANUFACTURE OF LEAD FRAME

(57)Abstract:

PURPOSE: To provide a semiconductor device having resin-sealed semiconductor chip and lead, manufacture thereof and manufacture of a lead frame used for the semiconductor device, wherein reliability of the semiconductor chip, standardization of an external electrode terminal, reduction in manufacturing cost and improvement in production efficiency may be realized.

CONSTITUTION: A semiconductor device has a semiconductor chip 2 having an electrode pad 6 at a first pitch, a lead 3 electrically connected with the electrode pad 6 via a wire 8, and seal resin 4 for sealing the semiconductor chip 2. In this semiconductor device, a protrusion 9 to be an external connection terminal is formed on the lead 3 at a second pitch different from the first pitch. The seal resin 4 seals the wire 8 arranged between the electrode pad 6 and the lead 3. Also, the protrusion 9 is exposed.

**LEGAL STATUS**